

# Model: BASIC LINE UTS

## Order number: 23-061150-401

Correct use: Passive storage



### **BASIC UTS BST-5 Type 30, safety cabinet with wing door**

Classical door technology (door handle), door hung right.

For the storage of flammable liquids.

Type testing by MPA according to DIN EN 14470-1

Mark of approval: CE mark

Construction and colour:

- Carcass of decor panels, RAL 7035
- Door of decor panels, RAL 7035

Fittings and features:

- Door closes automatically in case of fire
- Cylinder lock for safe access
- Bottom tray sheet steel, RAL 7035
- Perforated sheet insert, RAL 7035
- Exhaust air connection socket at the rear of the cabinet
- Visual inspection of the ventilation opening
- Earthing connection at the rear of the cabinet
- Interior fittings conductively connected with carcass
- Set-back base, RAL 7035

Further technical information:

[www.dueperthal.com](http://www.dueperthal.com)

Category: Type 30 - flammable liquids Model size: BLT-5, Outer height [mm]: 635, Outer width [mm]: 1.095, Outer depth [mm]: 500, Gross weight [kg]: 100,00, Net weight [kg]: 97,00, Number of storage levels: 1, Number of storage areas per storage level: 1, Door operation: classical technology, Door technology: wing door technology,