

### Main

Range	Affle Plus
Product or component type	Switch
Device application	Control switch
Load type	Resistive Inductive Fluorescent lamp Incandescent lamp
Colour tint	White

### Complementary

Device mounting	Flush
Switch function	2-way
Cable cross section	4 Mm <sup>2</sup> stranded cable 2.5 Mm <sup>2</sup> solid cable 2.5 Mm <sup>2</sup> stranded cable 6 x 4 mm <sup>2</sup> solid cable for AC
Rated current	10 AX at 250 V AC
Number of gangs	2 gangs
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: surround Polycarbonate: actuator
Connections - terminals	Screw terminal Brass terminal
Embedding depth	24.9 mm
Width	86 mm
Height	86 mm
Depth	35.6 mm

### Environment

Maximum ambient air temperature for operation	35 °C
Relative humidity	0...95 %
Operating altitude	5000 m
Product certifications	IEC
Standards	BS EN 60669-1 MS IEC 60669-1 IEC 60669-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	91 g
Package 1 Height	3.6 cm
Package 1 width	8.6 cm
Package 1 Length	8.6 cm
Unit Type of Package 2	BB1

Number of Units in Package 2	8
Package 2 Weight	732 g
Package 2 Height	9.5 cm
Package 2 width	15 cm
Package 2 Length	19 cm
Unit Type of Package 3	P12
Number of Units in Package 3	1536
Package 3 Weight	148.467 kg
Package 3 Height	100 cm
Package 3 width	80 cm
Package 3 Length	120 cm