



Chemical protection

ALTO 299

Prolonged contact (or immersion) | intermittent wear

Good mechanical performance for long-lasting chemical protection

SPECIFIC ADVANTAGES



Durability

- Longer service life and good impact protection, due to the thickness of the material

INDUSTRIES

- Mechanical industry
- Construction Industry (Heating engineers/Plumbers)
- Other industries

APPLICATIONS

- Emptying and cleaning septic tanks
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments



CHEMICAL PROTECTION
TYPE A

EN388



3121X

EN ISO 374-1



TYPE A
AKLMPT

EN ISO 374-5



CATEGORY 3



0334

DEXTERITY

EN420:
5/5






Chemical protection

ALTO 299

Prolonged contact (or immersion) | intermittent wear

LEGENDS



PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Natural latex
Cuff characteristic	Straight cuff
Colour.s	Orange
Length (cm)	31
Thickness (mm)	0.9
European sizes	7 8 9 10

LOGISTIC DETAILS

Packaging	1 pair/bag 5 pairs/bag 50 pairs/carton
-----------	--

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/126/09/18/2001
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France