















PIG® Caution Industrial Absorbent Adhesive-Backed Grippy® Floor Mat

MAT32400 Absorbs Oils; Coolants; Solvents; Water; Universal,32" W x 100' L,1 roll

Alert workers to slip or trip hazards around workstations and machinery with a high-visibility adhesive-backed absorbent mat featuring a repeating caution message; provides traction and safe footing in slip prone areas.

- Bright yellow color and caution message draw attention to potential slip hazards from leaks and drips around machinery, equipment, workstations and production areas, even in poorly lit areas
- Adhesive-backed mat stays exactly where you put it with no shifting, bunching up or flipping over to prevent slips, trips and falls
- Sticks to most commercial floor surfaces like cleaned and sealed concrete, vinyl tile, linoleum, ceramic tile and quarry tile
- Walk all over it! Tough, spunbond top layer with heavy-duty zigzag stitching stands up to foot and light-wheeled traffic; keep mat in service until it's saturated or shows signs of wear
- Makes it easy to sweep up debris like metal shavings and wood chips while also absorbing common industrial fluids
- Multiple layers of fine-fiber polypropylene safely absorb leaks, drips and overspray of oils, coolants, solvents and water to keep them from being tracked around
- Leakproof backing prevents absorbed liquid from soaking through to the floor for easier change outs and floor protection
- Easy to cut and install: just roll it out, cut to size, stick it down and apply pressure to smooth it out
- Align seams end to end or side by side to cover large areas; do not overlap seams to avoid premature lifting
- Proprietary adhesive sticks to the floor with a super-tight grip, but peels up easily for quick changeouts; reduces cleanup time to make your facility more productive
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Caution Grippy Mat have been proven to reduce slip-and-fall claims by as

much as 90%

- Mats take on the properties of absorbed liquids
 - always take proper precautions when handling saturated absorbents
- See Resources &Downloads section for product use guidance







Item#	Description	Dimensions	Weight
MAT32400-YW		32" W x 100' L	31 lbs.
Metric Equivalent:			
Item#	Description	Dimensions	Weight
MAT32400-YW		81cm W x 30m L	14.1 kg
Specifications			
		10 10 0 col	
Absorbency Range Dimensions		10 - 19.9 gal. 32" W x 100' L	
Mat Weight		Mediumweight	ant.
Recycled Content		25% or more Recycled Conte	ent
Absorbency		Up to 10.5 gal. per roll	
Brand		PIG	Mark
Category		Grippy® Industrial Absorbent	
Flammability Specifications		Flame Resistant - Will melt a	
Fluid Absorbed		Oils; Coolants; Solvents; Wat	er; Universal
Incinerable		Yes	
Industry		Industrial Facilities; Shops &	Garages
Intended Use		Indoor Use on Concrete, Viny Flooring	/l, Linoleum, Tile and Laminate
Perforated		No	
Storage Temp Range		Store between 32°F and 120°	°F
Temperature Limit		Surface temps from 55°F to 1	20°F
Traffic		Light Foot Traffic	
UV Resistant		No	
Sold as		1 roll	
Weight		31 lbs.	
# per Pallet		12	
Composition		Absorbent: Polypropylene Stitching: Polyester	

	Adhesive Backing: Proprietary Adhesive Material
UNSPSC	47131901
Pigalog® Page Number	Page 221

Metric Equivalent

Absorbency	Up to 39.7 L per roll
Weight	14.1 kg
Dimensions	81cm W x 30m L

Technical Information

Certifications, Approvals and Ratings

NFSI Certified, ANSI B101.1-2009, ANSI/ESD STM11.11, MIL-STD-3010C

Technical Documents

PIG Grippy® Absorbent Mat

The Complete Slip, Trip & Fall Risk Zone Audit

New Pig Adhesive-Backed Mat Disclaimer and Warranty Info

How to use PIG Grippy Absorbent Mat

Technical Data Sheet for PIG® Adhesive-Backed Grippy Mat

White Paper- The Walk Zone Safety Report

29 CFR 1910.22(a)(2)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com