

# Product datasheet

Specifications



## Switched Socket, Vivace, 15A, 250V, 1 gang, white

KB15\_15\_WE

### Main

Range	Vivace
Product or component type	Switched socket
Device short name	KB15
Device application	Power supply Control
Device presentation	Complete product
Switch application	On/off switching
Main colour tint	White
Colour tint	White

### Complementary

Outlet poles configuration	2P + E
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	22.0 mm
Rated current	15 A at 250 V AC, resistive
Network frequency	50/60 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L Earth N
Tightening torque	0.4 N.m
clamping connection capacity	2.5 mm <sup>2</sup>
Width	87 mm
Height	87 mm

---

Depth	35 mm
-------	-------

## Environment

---

Standards	MS 589 SS 145 BS 1362-2
-----------	-------------------------------

---

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

---

Ambient air temperature for storage	-5...60 °C
-------------------------------------	------------

---

Relative humidity	0...95 %
-------------------	----------

---

Operating altitude	<= 2000 m
--------------------	-----------

---

Environmental characteristic	Indoor use
------------------------------	------------

---

IP degree of protection	IP20
-------------------------	------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	8.6 cm
------------------	--------

---

Package 1 Width	3.2 cm
-----------------	--------

---

Package 1 Length	8.6 cm
------------------	--------

---

Package 1 Weight	118 g
------------------	-------

---

Unit Type of Package 2	BB1
------------------------	-----

---

Number of Units in Package 2	10
------------------------------	----

---

Package 2 Height	9.5 cm
------------------	--------

---

Package 2 Width	15 cm
-----------------	-------

---

Package 2 Length	19 cm
------------------	-------

---

Package 2 Weight	1.25 kg
------------------	---------

---

Unit Type of Package 3	CAR
------------------------	-----

---

Number of Units in Package 3	100
------------------------------	-----

---

Package 3 Height	31.5 cm
------------------	---------

---

Package 3 Width	50 cm
-----------------	-------

---

Package 3 Length	50 cm
------------------	-------

---

Package 3 Weight	12054 g
------------------	---------

## Contractual warranty

---

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations