

13PA/S&L – Aluminized Overcoat

70% pre-oxidate + 30% para-aramid alluminized SOFT & LIGHT ,Overcoat;
mandarin collar, button on wrist.

Front closure with snaps covered by a tearing strip.

Standard length 120 cm

AVAILABLE SIZES:

COAT MEASURES							
cm	½ CHEST	½ WAISTLINE	½ HIP	SHOULDER WIDTH	SHOULDER	SLEEVE LENGTH	LENGTH * (without collar)
S	63	64	65.5	53.8	18.9	67.5	117
M	65	66	67.5	54.9	19.2	68.5	118.5
L	67	68	69.5	56	19.5	69.5	120
XL	69	70	71.5	57.1	19.8	70.5	121.5
XXL	71	72	73.5	58.2	20.1	71.5	123
3XL	73	74	75.5	59.3	20.4	72.5	124.5
4XL	75	76	77.5	60.4	20.7	73.5	126



GIORDANI
GIANCARLO
WORK PROTECTION ITEMS

FEATURES OVERCOATS

USES:

Clothing to be worn against small flames, low values of convective and radiant heat, molten metal splashes.

Other uses than those listed above are excluded.

Possibility to customize the PPE :

- *Front or back opening or back closure at the shoulder blades;*
- *Breathable back side;*
- *Fastening flap for adjustable cuff*
- *Air ventilation under armhole*
- *Side pleats at garment bottom*
- *Length 110 cm, 120 cm, 130 cm, 140 cm, 150 cm*



STANDARDS:

UNI EN ISO 13688:2013

Protective clothing – general requirements

UNI EN ISO 16112:2015

Protective clothing to protect against heat
and Flame

Performances: **A1 B1 C3 D3 E3 F1**

PPE 3° CATEGORY