

## Sure-Grip® EX Slimline Safety Cabinets

Safely store flammables when floor space is tight or use to expand storage alongside existing cabinets

- Fire tested and approved by FM Approvals; complies with OSHA and NFPA
- 18-gauge (1-mm) thick double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space
- 3-point stainless steel bullet latching system
- U-Loc<sup>™</sup> handle with two keys—accepts optional padlock
- Adjustable, patented SpillSlope® galvanized steel shelves direct spills to 2-in (51-mm) leakproof sump
- Trilingual warning with Haz-Alert™ reflective labels
- Includes dual vents with flame arresters, adjustable leveling feet, grounding connector
- Self-closing models equipped with fusible link holds door open during use and melts at 165 F (74 C) to automatically close under fire conditions



	Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Yellow Model	Red Model	Gray Model	White Model	CA Prop 65
	22/83	1 door, manual	65 x 23.25 x 18 in 1651 x 591 x 457 mm	3	FM, N, O, A	892200	892201	892203	892205	
	(standard)	1 door, self-close			FM, N, O, A, I	892220	892221	892223	892225	<u>^</u>
	54/204	1 door, manual	65 x 23.25 x 34 in 1651 x 591 x 864 mm		FM, N, O, A	895400	895401	895403	895405	
	(deep)	1 door, self-close			FM, N, O, A, I	895420	895421	895423	895425	<u>^</u>

Accessories	Fits Cabinet Styles	W x D	Model	
CnillClang® atool abolf	22 gallon (83 L) slimline	19.625 x 14 in (498 x 356 mm)	29936	
SpillSlope® steel shelf	54 gallon (204 L) deep slimline	19.625 x 29 in (498 x 737 mm)	29941	

<sup>▲</sup> WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.