


Product Data Sheet

MaxiChem® 56-630

| | |
|-------------------------|--------------------------------|
| Colour – Coating | Green/black |
| Colour – Liner | White |
| Design | Gauntlet - 30 cm |
| Coating | NBR (Nitrile Butadiene Rubber) |
| Coating texture | Micro-Foam with Non-Slip Grip |
| Liner | Nylon |
| Patent number | EP 1 608 808 |
| Palm thickness | 1.30 mm |



Dimensions

| Size Range | Size 7 (S) | Size 8 (M) | Size 9 (L) | Size 10 (XL) | Size 11 (XXL) |
|-------------------------------|------------|------------|------------|--------------|---------------|
| Total glove length (+/-10 mm) | 300 | 300 | 300 | 300 | 300 |
| Wrist length (mm) | | | | | |
| Wrist width (mm) | | | | | |
| Palm width (+/-3 mm) | 104 | 109 | 111 | 116 | 120 |
| Over lock colour | Red | Orange | White | Yellow | Black |

EN test Results

| Test | Notified Body | Result/Pass |
|---------------------------|---------------|-------------|
| EN ISO 374-1: 2016/Type A | TÜV Rheinland | JKLMNO |
| EN ISO 374-5: 2016 | TÜV Rheinland | Yes |
| EN ISO 21420: 2020 | TÜV Rheinland | Yes |
| EN 388: 2016 + A1: 2018 | TÜV Rheinland | 4121A |



Product Data Sheet

MaxiChem® 56-630

Typical Performance Values

| | |
|--|--|
| EN ISO 374-1:2016 J - n-Heptane | 6 (>480 min) |
| EN ISO 374-1:2016 K - Sodium hydroxide 40% | 6 (>480 min) |
| EN ISO 374-1:2016 L - Sulphuric acid 96% | 4 (>120 min) |
| EN ISO 374-1:2016 M - Nitric acid 65% | 4 (>120 min) |
| EN ISO 374-1:2016 N - Acetic acid 99% | 3 (>60 min) |
| EN ISO 374-1:2016 O - Ammonia 25% | 6 (>480 min) |
| EN ISO 374-1:2016 Protective gloves against dangerous chemical risks | The permeation performance shall be at least level 2 against a minimum of six test chemicals |
| EN ISO 374-5:2016 Protective gloves against microorganisms | Yes |
| EN ISO 21420 Dexterity | Level 5 |
| EN 388:2016 + A1:2018 A. Abrasion Resistance | > 8000 Cycles |
| EN 388:2016 + A1:2018 B. Cut Resistance | > 1.2 index |
| EN 388:2016 + A1:2018 C. Tear Resistance | > 25 newtons |
| EN 388:2016 + A1:2018 D. Puncture Resistance | > 20 newtons |
| EN 388:2016 + A1:2018 E. Cut Resistance ISO | ≥ 2 Newton |

HandCare®

| | |
|--|-----------|
| Skin Health Alliance Dermatologically Accredited | Yes |
| REACH compliant | Yes |
| Oeko-Tex® 100 | Certified |
| Sanitized® | Yes |



Product Data Sheet

MaxiChem® 56-630

Special features

| | |
|---------------|-----|
| Silicone free | Yes |
|---------------|-----|

Packaging

| | |
|------------------------|-----------------|
| Pairs per poly bag | 12 |
| Poly bags per carton | 6 |
| Carton count | 72 |
| Carton dimensions (mm) | 500 x 295 x 270 |

Weight

| Size Range | Size 7 (S) | Size 8 (M) | Size 9 (L) | Size 10 (XL) | Size 11 (XXL) |
|---------------------------------|------------|------------|------------|--------------|---------------|
| Glove weight / Pair (+/-6 gram) | 96 | 102 | 112 | 120 | 122 |
| Gross Weight (Kg) | 9.5 | 10.2 | 10.7 | 11 | 11.5 |
| Carton Weight (Kg) | 1 | 1 | 1 | 1 | 1 |
| Net Weight (Kg) | 8.5 | 9.2 | 9.7 | 10 | 10.5 |

Issue date: 30.01.2019

